Rule DAS285: APPLICATIONS ACCESSING VOLUME DURING MEASUREMENT INTERVAL WITH WORST PERFORMANCE

Finding: CPExpert identifies the applications (other than the "loved one" workload)

accessing the volume during the the measurement interval with the worst

performance.

Impact: This finding is used to select applications for potential rescheduling, file

movement, or design changes.

Logic flow: The following rules cause this rule to be invoked:

DAS200: Volume with worst overall performance

Discussion: CPExpert lists the applications accessing the volume with the worst

performance during the measurement period with the worst performance being analyzed. The list is ordered descendingly by I/O operations, so you can identify the applications which probably had the most impact on the

volume.

As described in Section 5, the SMF Type 30(Interval) information is not synchronized with the SMF Type 70(series) information. Consequently, the identification of applications may not correctly identify the applications with

the most I/O operations to the volume.

However, if the analysis produces the same results after analyzing more than one day's measurement data, you can be more comfortable that the

applications are correctly identified.

Suggestion: In many cases, once the applications are identified, either applications

personnel or systems personnel will verify whether the particular applications are responsible for the majority of the I/O operations to the

particular volume.

Once you are comfortable that the applications are responsible for the majority of the I/O operations to the "worst" performing device, you can take action to (1) reschedule the applications to minimize contention, (2) examine the files referenced by the applications, or (3) change the way in

which the applications access their files.